

NFS Wedgegard® Coupling Standard Torque Table



CODES	S350 - 110		S500 - 125		S700 - 180		S700 - 225		S950 - 250	
	W37		W50		W50		W50		W100	
	B	S	B	S	B	S	B	S	B	S
O	45	62	52	71	126	173	126	173	–	–
OW	62	85	72	99	191	274	191	274	–	–
GD	84	115	97	134	–	–	–	–	–	–
W	116	159	135	185	275	377	275	377	830	1140
WY	167	230	194	266	373	512	373	512	1165	1600
Y	221	303	256	352	487	705	487	705	1475	2030
YB	293	402	340	467	712	978	712	978	2010	2760
BN	303	–	352	–	–	–	–	–	–	–
B	345	474	400	549	978	1344	978	1344	2400	3300
BG	402	552	467	640	1222	1678	1222	1678	2850	3900
G	497	682	576	791	1494	2050	1494	2050	3600	4900
RG	601	825	697	957	1886	2589	1886	2589	4200	5700
R	676	928	784	1076	1950	2678	1950	2678	4800	6600
RK	–	–	–	–	–	–	–	–	–	–
K	–	–	–	–	2032	2791	2032	2791	5600	7650

*Ratings are per single Wedgepin fitted.

*Dimensions and specifications may change for improvement without notice.

*Ratings are in Nm and approximate.