

S250 - S1600 Wedgegard® Standard Torque Table



CODES	S250		S350		S500		S700		S800		S950		S1000		S1200		S1400		S1600	
	W37		W37		W50		W50		W50		W100		W100		W100		W100		W100	
	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S
O	-	-	45	62	52	71	126	173	148	203	-	-	-	-	-	-	-	-	-	-
OW	-	-	62	85	72	99	191	274	224	321	-	-	-	-	-	-	-	-	-	-
GD	-	-	84	115	97	134	-	-	-	-	-	-	-	-	-	-	-	-	-	-
W	-	25	116	159	135	185	275	377	322	442	830	1140	-	3470	-	3980	-	-	-	-
WY	-	40	167	230	194	266	373	512	437	601	1165	1600	-	5160	-	5920	-	-	-	-
Y	-	80	221	303	256	352	487	705	572	827	1475	2030	-	6940	-	7970	-	12240	-	15300
YB	-	-	293	402	340	467	712	978	836	1148	2010	2760	-	8720	-	10000	-	-	-	-
BN	-	-	303	-	352	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B	-	110	345	474	400	549	978	1344	1148	1577	2400	3300	-	9820	-	11280	-	17630	-	22040
BG	-	-	402	552	467	640	1222	1678	1434	1969	2850	3900	-	11610	-	13330	-	-	-	-
G	-	135	497	682	576	791	1494	2050	1753	2405	3600	4900	-	13880	-	15930	-	20240	-	25300
RG	-	-	601	825	697	957	1886	2589	2213	3038	4200	5700	-	-	-	-	-	-	-	-
R	-	170	676	928	784	1076	1950	2678	2288	3143	4800	6600	-	15980	-	18350	-	25000	-	31240
RK	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
K	-	-	-	-	-	-	2032	2791	2385	3274	5600	7650	-	16920	-	19430	-	31340	-	39180

*Ratings are per single Wedgepin fitted.

*Dimensions and specifications may change for improvement without notice.

*Ratings are in Nm and approximate.