

# CFS Wedgegard® Standard Torque Table



CODES	S350 - 135		S500 - 160		S500 - 198		S700 - 220		S700 - 275		S950 - 350		S1000 - 425	
	W37		W50		W50		W50		W50		W100		W100	
	B	S	B	S	B	S	B	S	B	S	B	S	B	S
O	45	62	52	71	52	71	126	173	126	173	-	-	-	-
OW	62	85	72	99	72	99	191	274	191	274	-	-	-	-
GD	84	115	97	134	97	134	-	-	-	-	-	-	-	-
W	116	159	135	185	135	185	275	377	275	377	830	1140	-	3470
WY	167	230	194	266	194	266	373	512	373	512	1165	1600	-	5160
Y	221	303	256	352	256	352	487	705	487	705	1475	2030	-	6940
YB	293	402	340	467	340	467	712	978	712	978	2010	2760	-	8720
BN	303	-	352	-	352	-	-	-	-	-	-	-	-	-
B	345	474	400	549	400	549	978	1344	978	1344	2400	3300	-	9820
BG	402	552	467	640	467	640	1222	1678	1222	1678	2850	3900	-	11610
G	497	682	576	791	576	791	1494	2050	1494	2050	3600	4900	-	13880
RG	601	825	697	957	697	957	1886	2589	1886	2589	4200	5700	-	-
R	676	928	784	1076	784	1076	1950	2678	1950	2678	4800	6600	-	15980
RK	-	-	-	-	-	-	-	-	-	-	-	-	-	-
K	-	-	-	-	-	-	2032	2791	2032	2791	5600	7650	-	16920

\*Ratings are per single Wedgepin fitted.

\*Dimensions and specifications may change for improvement without notice.

\*Ratings are in Nm and approximate.