



Chain Type Wedgegard Couplings are supplied bored and keywayed to customer requirements..

Standard Units for release torques up to 64,000 Nm. Torque is adjustable by Wedgepin ratings.

Designs to suit special drive requirements are available.

Standard natural finish on Wedgegard unit and chain coupling, chemical blacking as an option.

All dimensions in mm.

Model	Misalignment		Nom Drive Nm	Max Release Nm	Wedgepin	PWR	Dia (A)	Bores		Length (L)
	Parallel	Angular						B1 Max	B2 Max	
S350	0.31 mm	½°	<b>2785</b>	<b>1500</b>	3 x W37	47	145	57	35	106
S500	0.38 mm	½°	<b>3230</b>	<b>2000</b>	3 x W37	54.5	195	70	50	119
S700	0.51 mm	½°	<b>7700</b>	<b>5500</b>	3 x W50	66	240	102	70	162
S950	0.75 mm	½°	<b>21555</b>	<b>14000</b>	3 x W75	105.5	320	150	100	216
S1000	1 mm	½°	<b>64000</b>	<b>38000</b>	4 x W100	128	470	200	115	286

\*All figures are approximate.

\*Dimensions in mm unless otherwise shown.

\*Dimensions and specifications may change for improvement without notice.