

S250 - S1600 Wedgegard® Standard Torque Table



CODES	S250		S350		S500		S700		S800		S950		S1000		S1200		S1400		S1600	
	W37		W37		W50		W50		W50		W100		W100		W100		W100		W100	
	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S	B	S
O	-	-	33	45	38	52	93	128	109	150	-	-	-	-	-	-	-	-	-	-
OW	-	-	46	63	53	73	141	202	165	237	-	-	-	-	-	-	-	-	-	-
GD	-	-	62	85	71	99	-	-	-	-	-	-	-	-	-	-	-	-	-	-
W	-	18	86	118	99	136	203	278	238	326	612	841	-	2559	-	2935	-	-	-	-
WY	-	30	123	170	143	196	275	378	323	443	859	1180	-	3806	-	4366	-	-	-	-
Y	-	59	163	224	189	260	359	520	422	610	1088	1497	-	5119	-	5878	-	9028	-	11285
YB	-	-	216	297	251	344	525	722	616	847	1482	2036	-	6432	-	7376	-	-	-	-
BN	-	-	223	-	260	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B	-	81	254	349	295	405	722	991	847	1163	1770	2434	-	7243	-	8320	-	13004	-	16256
BG	-	-	297	407	344	472	901	1238	1058	1452	2102	2876	-	8563	-	9832	-	-	-	-
G	-	99	366	503	425	583	1102	1512	1293	1774	2655	3614	-	10238	-	11750	-	14929	-	18661
RG	-	-	443	609	514	706	1391	1910	1632	2241	3098	4204	-	-	-	-	-	-	-	-
R	-	125	498	685	578	794	1438	1975	1688	2318	3540	4868	-	11786	-	13535	-	18435	-	23042
RK	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
K	-	-	-	-	-	-	1499	2058	1759	2415	4130	5642	-	12480	-	14331	-	23116	-	28898

*Ratings are per single Wedgepin fitted.

*Dimensions and specifications may change for improvement without notice.

*Ratings are in ft-lb and approximate.